

HRP56N08K 80V N-Channel Trench MOSFET

Features

- Low Dense Cell Design
- Reliable and Rugged
- Advanced Trench Process Technology
- 100% UIS Tested, 100% Rg Tested
- Lead free, Halogen Free


Application

- Power Management in Inverter System
- Synchronous Rectification

Key Parameters

Parameter	Value	Unit
BV _{DSS}	80	V
I _D	140	A
R _{DS(on)} , Typ	4.4	mΩ
Q _{g, Typ}	110	nC

Package & Internal Circuit



Absolute Maximum Ratings

T_J=25°C unless otherwise specified

Symbol	Parameter		Value	Units
V _{DSS}	Drain-Source Voltage		80	V
V _{GS}	Gate-Source Voltage		±25	V
I _D	Drain Current		140	A
	T _C = 100°C	100	A	
I _{DM}	Pulsed Drain Current		560	A
E _{AS}	Single Pulsed Avalanche Energy L=1mH		510	mJ
E _{AR}	Repetitive Avalanche Energy		27.2	W
P _D	Power Dissipation	T _C = 25°C	272	W
T _J , T _{STG}	Operating and Storage Temperature Range		-55 to +175	°C

Thermal Resistance Characteristics

Symbol	Parameter	Typ.	Max.	Units
R _{θJC}	Junction-to-Case	--	0.55	°C/W
R _{θJA}	Junction-to-Ambient	--	62.5	°C/W

Electrical Characteristics $T_J=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
On Characteristics						
V_{GS}	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 250 \mu\text{A}$	2.0	--	4.0	V
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS} = 10 \text{ V}$, $I_D = 40 \text{ A}$	--	4.4	5.5	$\text{m}\Omega$
g_{FS}	Forward Transconductance	$V_{DS} = 20 \text{ V}$, $I_D = 40 \text{ A}$	--	80	--	S
Off Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}$, $I_D = 250 \mu\text{A}$	80	--	--	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 64 \text{ V}$, $V_{GS} = 0 \text{ V}$	--	--	1	μA
		$V_{DS} = 64 \text{ V}$, $T_J = 100^\circ\text{C}$	--	--	100	μA
I_{GSS}	Gate-Body Leakage Current	$V_{GS} = \pm 25 \text{ V}$, $V_{DS} = 0 \text{ V}$	--	--	± 100	nA
Dynamic Characteristics						
C_{iss}	Input Capacitance	$V_{DS} = 25 \text{ V}$, $V_{GS} = 0 \text{ V}$, $f = 1.0 \text{ MHz}$	--	4700	--	pF
C_{oss}	Output Capacitance		--	620	--	pF
C_{rss}	Reverse Transfer Capacitance		--	400	--	pF
R_g	Gate Resistance	$V_{GS} = 0 \text{ V}$, $V_{DS} = 0 \text{ V}$, $f = 1 \text{ MHz}$	--	1.7	--	Ω
Switching Characteristics						
$t_{d(on)}$	Turn-On Time	$V_{DS} = 40 \text{ V}$, $I_D = 30 \text{ A}$, $R_G = 6 \Omega$	--	65	--	ns
t_r	Turn-On Rise Time		--	70	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	190	--	ns
t_f	Turn-Off Fall Time		--	50	--	ns
Q_g	Total Gate Charge	$V_{DS} = 64 \text{ V}$, $I_D = 30 \text{ A}$, $V_{GS} = 10 \text{ V}$	--	110	--	nC
Q_{gs}	Gate-Source Charge		--	24	--	nC
Q_{gd}	Gate-Drain Charge		--	44	--	nC
Source-Drain Diode Characteristics						
V_{SD}	Source-Drain Diode Forward Voltage	$I_S = 30 \text{ A}$, $V_{GS} = 0 \text{ V}$	--	--	1.3	V
trr	Reverse Recovery Time	$I_S = 30 \text{ A}$, $V_{GS} = 0 \text{ V}$ $dI_F/dt = 100 \text{ A}/\mu\text{s}$	--	60	--	ns
Qrr	Reverse Recovery Charge		--	100	--	nC

Typical Characteristics




Figure 1. On Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On Resistance Variation vs. Drain Current and Gate Voltage




Figure 4. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics

Typical Characteristics (continued)




Figure 7. On-Resistance Variation vs Gate-Source Voltage




Figure 8. On-Resistance Variation vs Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs Case Temperature




Figure 11. Transient Thermal Response Curve








Fig 12. Gate Charge Test Circuit & Waveform**Fig 13. Resistive Switching Test Circuit & Waveforms****Fig 14. Unclamped Inductive Switching Test Circuit & Waveforms**

Fig 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms



Package Dimension**TO-220**